#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau

18 August 2005 (18.08.2005)

(43) International Publication Date



# 

**PCT** 

## (10) International Publication Number WO 2005/075843 A1

(51) International Patent Classification7: 27/04, 27/06

F16C 33/58,

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,

GQ, GW, ML, MR, NE, SN, TD, TG).

(84) Designated States (unless otherwise indicated, for every

(21) International Application Number:

PCT/BE2005/000013

(22) International Filing Date: 2 February 2005 (02.02.2005)

(71) Applicant (for all designated States except US): HANSEN

TRANSMISSIONS INTERNATIONAL, naamloze ven-

nootschap [BE/BE]; Leonardo Da Vincilaan 1, B-2650

Gregory [ZA/BE]; Vuurgatstraat 68, B-3090 Overijse

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0402255.4

Edegem (BE).

3 February 2004 (03.02.2004) GB Declarations under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS. JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, Cl, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

(74) Agent: DONNÉ, E.; Bureau M.F.J. Bockstael nv., Aren-

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

bergstraat 13, B-2000 Antwerpen (BE).


of inventorship (Rule 4.17(iv)) for US only

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ROLLER BEARING



(57) Abstract: A roller bearing (10) comprises a plurality of bearing rollers (12) located between confronting bearing surfaces (16, 19), said bearing surfaces being rotatable one relative to the other about the rotational axis of the bearing, and said bearing comprising biasing means (18) which provides a force acting in a direction between said confronting bearing surfaces (16, 19) whereby, under all load conditions for which the bearing is designed for use, each bearing roller is retained in contact with each of said confronting bearing surfaces.

